

DH-PFS3110-8T

8-Port Ethernet Switch (Unmanaged)



Features

- > 2-layer industrial level switch
- > Conform IEEE802.3, IEEE802.3u, IEEE802.3ab/z and IEEE802.3X standards
- > 100M/1000M self-adaptive SFP fiber port
- > Industrial wide temperature design

Technical Specifications

Model	DH-PFS3110-8T
Ethernet port	1*100/1000 Base-X、 1*10/100/1000 Base-T、 8*10/100 Base-T
Switching Capacity	13.6G
Packet Forwarding Rate	4.17Mpps
Packet Buffer Memory	2Mb
MAC Table Size	8K
Exchange Mode	Store & forward

DH-PFS3110-8T

Application Humidity	10%—90%
Power	DC 12V
Power Consumption	≤3W
Lightning Protection	Common Mode 4KV Differential Mode 2KV
Working Temperature	- 40℃~70℃
Weight	540g
Dimension(W×D×H)	150mm×100mm×42mm

Accessories

Model	
PFT3950	1.25G 850nm,500m,LC, Multi-mode
PFT3960	1.25G 1310/1550nm,20km,LC, Single-mode
PFT3970	1.25G 1550/1310nm,20km,LC, Single-mode

Dahua Technology Co., Ltd.

1187 BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Fax: +86-571-87688815

Email:overseas@dahuatech.com

www.dahuatech.com

*Design and specifications are subject to change without notice.

© 2012 Dahua Technology Co., Ltd.